

DECLARATION OF PERFORMANCE

Hawkshaw

Ref: 2026-533



1.	Unique identification code or name:	Hawkshaw
2.	Intended use:	Heating systems in buildings
3.	Registered name:	Double Quick (Heating) Ltd Units 3 & 4 St Helens House St Helens Way, Thetford, Norfolk IP24 1HG.
4.	Systems of assessment:	System 3
5.	Harmonised standard:	BS EN 442-1:2014
5a.	Testing facility:	HEATEST, s.r.o. Býkev 84, 276 01 Mělník, Czech Republic - No. 2693
5b.	Test Report No:	006/2023

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	A1
Release of dangerous substances	None
Maximum operating pressure	400
Pressure tightness	No leakage at 1,30 x MOP
Resistance to pressure	No breakage at 1,69 x MOP
Maximum surface temperature	110°C
Rated thermal outputs (per section)	Please see table below
Resistance against corrosion	Absence of surface corrosion after 100 h humidity
Resistance against minor impact	Class 0

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

S C Double
Managing Director



Dated January 2026



Dimensions and Thermal Outputs | 4 COLUMN

CODE	HEIGHT (mm)	WIDTH (mm)	OUTPUT (WATTS)	
			ΔT 50°C	ΔT 30°C
HAWK460/10	460	665	620	319
HAWK460/14	460	905	868	447
HAWK460/18	460	1145	1116	575
HAWK660/10	660	665	820	422
HAWK660/14	660	905	1148	591
HAWK660/18	660	1145	1476	760
HAWK760/10	760	665	1060	546
HAWK760/14	760	905	1484	764
HAWK760/18	760	1145	1908	983

This product is Made to Measure, the ratings in the above table refer to 1 section only.

