

DECLARATION OF PERFORMANCE

Cove

Ref: 2026-535



1.	Unique identification code or name:	Cove
2.	Intended use:	Heating systems in buildings
3.	Registered name:	Double Quick (Heating) Ltd Units 3 & 4 St Helens House St Helens Way, Thetford, Norfolk IP24 1HG.
4.	Systems of assessment:	System 3
5.	Harmonised standard:	BS EN 442-1:2014
5a.	Testing facility:	BSRIA Limited, Old Bracknell Lane West, Bracknell, Berkshire, RG12 7AH, UK - No. 0480
5b.	Test Report No:	101367/1

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	A1
Release of dangerous substances	None
Maximum operating pressure	600
Pressure tightness	No leakage at 1,30 x MOP
Resistance to pressure	No breakage at 1,69 x MOP
Maximum surface temperature	110°C
Rated thermal outputs	Please see table below
Resistance against corrosion	Absence of surface corrosion after 100 h humidity
Resistance against minor impact	Class 0

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

S C Double
Managing Director



Dated January 2026



Dimensions and Thermal Outputs | **DOUBLE**

CODE	HEIGHT (mm)	WIDTH (mm)	OUTPUT (WATTS)	
			ΔT 50°C	ΔT 30°C
COVE150/5D	1500	295	800	412
COVE150/7D	1500	413	1130	582
COVE180/5D	1800	295	970	500
COVE180/7D	1800	413	1350	695
COVE180/9D	1800	531	1740	896
COVE550/7D	550	413	440	227
COVE550/10D	550	590	625	322
COVE550/14D	550	826	880	453
COVE550/17D	550	1003	1065	548
COVE550/20D	550	1180	1250	644
COVE550/24D	550	1412	1500	773

Dimensions and Thermal Outputs | **SINGLE**

CODE	HEIGHT (mm)	WIDTH (mm)	OUTPUT (WATTS)	
			ΔT 50°C	ΔT 30°C
COVE150/5	1500	295	530	273
COVE150/7	1500	413	750	386
COVE180/5	1800	295	640	330
COVE180/7	1800	413	895	461
COVE180/9	1800	531	1155	595
COVE550/7	550	413	275	142
COVE550/10	550	590	390	201
COVE550/14	550	826	550	283
COVE550/17	550	1003	665	342
COVE550/20	550	1180	780	402
COVE550/24	550	1412	936	482

