

DECLARATION OF PERFORMANCE

Osset

Ref: 2026-540



1.	Unique identification code or name:	Osset
2.	Intended use:	Heating systems in buildings
3.	Registered name:	Double Quick (Heating) Ltd Units 3 & 4 St Helens House St Helens Way, Thetford, Norfolk IP24 1HG.
4.	Systems of assessment:	System 3
5.	Harmonised standard:	BS EN 442-1:2014
5a.	Testing facility:	Laboratoria Misure Ricerche Termotecniche M.R.T, Via Raffaele Lambruschini, 4 (Zona Bovisa) - 20156, Milano, Italy - No. 1695
5b.	Test Report No:	ENE/MRT.RES.18333

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	A1
Release of dangerous substances	None
Maximum operating pressure	2000
Pressure tightness	No leakage at 1,30 x MOP
Resistance to pressure	No breakage at 1,69 x MOP
Maximum surface temperature	110°C
Rated thermal outputs	Please see table below
Resistance against corrosion	Absence of surface corrosion after 100 h humidity
Resistance against minor impact	Class 0

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

S C Double
Managing Director



Dated January 2026



Dimensions and Thermal Outputs |

CODE	HEIGHT (mm)	WIDTH (mm)	OUTPUT (WATTS)	
			ΔT 50°C	ΔT 30°C
OSSET431/5	431	420	432	222
OSSET431/7	431	580	605	312
OSSET431/10	431	820	864	445
OSSET431/12	431	980	1037	534
OSSET431/14	431	1140	1210	623
OSSET581/5	581	420	577	297
OSSET581/7	581	580	808	416
OSSET581/10	581	820	1154	594
OSSET581/12	581	980	1385	713
OSSET581/14	581	1140	1616	832
OSSET681/5	681	420	641	330
OSSET681/7	681	580	897	462
OSSET681/10	681	820	1282	660
OSSET681/12	681	980	1538	792
OSSET681/14	681	1140	1794	924