



Designer Radiators
and Towel Rails

DECLARATION OF PERFORMANCE

Metro

Ref: 2026-542



1.	Unique identification code or name:	Metro
2.	Intended use:	Heating systems in buildings
3.	Registered name:	Double Quick (Heating) Ltd Units 3 & 4 St Helens House St Helens Way, Thetford, Norfolk IP24 1HG.
4.	Systems of assessment:	System 3
5.	Harmonised standard:	BS EN 442-1:2014
5a.	Testing facility:	Laboratoria Misure Ricerche Termotecniche M.R.T, Via Raffaele Lambruschini, 4 (Zona Bovisa) - 20156, Milano, Italy - No. 1695
5b.	Test Report No:	ENE/MRT.RAP.13309

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	A1
Release of dangerous substances	None
Maximum operating pressure	500
Pressure tightness	No leakage at 1,30 x MOP
Resistance to pressure	No breakage at 1,69 x MOP
Maximum surface temperature	110°C
Rated thermal outputs	Please see table below
Resistance against corrosion	Absence of surface corrosion after 100 h humidity
Resistance against minor impact	Class 0

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

S C Double
Managing Director



Dated January 2026



Dimensions and Thermal Outputs |

CODE	HEIGHT (mm)	WIDTH (mm)	OUTPUT (WATTS)	
			ΔT 50°C	ΔT 30°C
METRO30/80	800	300	325	167
METRO30/120	1200	300	490	252
METRO40/80	800	400	370	191
METRO40/120	1200	400	530	273
METRO40/180	1800	400	840	433
METRO50/80	800	500	420	216
METRO50/120	1200	500	600	309
METRO50/150	1500	500	750	386
METRO50/180	1800	500	925	476
METRO60/80	800	600	445	229
METRO60/120	1200	600	710	366
METRO60/150	1500	600	900	464
METRO60/180	1800	600	1107	570