

DECLARATION OF PERFORMANCE

Herbie 2, 3 & 4 Column

Ref: 2026-569



1.	Unique identification code or name:	Herbie 2, 3 & 4 Column
2.	Intended use:	Heating systems in buildings
3.	Registered name:	Double Quick (Heating) Ltd Units 3 & 4 St Helens House St Helens Way, Thetford, Norfolk IP24 1HG.
4.	Systems of assessment:	System 3
5.	Harmonised standard:	BS EN 442-1:2014
5a.	Testing facility:	BSRIA Limited, Old Bracknell Lane West, Bracknell, Berkshire, RG12 7AH, UK - No. 0480
5b.	Test Report No:	105774

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	A1
Release of dangerous substances	None
Maximum operating pressure	400
Pressure tightness	No leakage at 1,30 x MOP
Resistance to pressure	No breakage at 1,69 x MOP
Maximum surface temperature	110°C
Rated thermal outputs (per section)	Please see table below
Resistance against corrosion	Absence of surface corrosion after 100 h humidity
Resistance against minor impact	Class 0

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

S C Double
Managing Director



Dated January 2026



Dimensions and Thermal Outputs | 2 COLUMN

CODE	HEIGHT (mm)	WIDTH (mm)	OUTPUT (WATTS)	
			ΔT 50°C	ΔT 30°C
CR/HER2/500	500	60	47	24
CR/HER2/650	650	60	53	27
CR/HER2/750	750	60	61	31.1

Dimensions and Thermal Outputs | 3 COLUMN

CODE	HEIGHT (mm)	WIDTH (mm)	OUTPUT (WATTS)	
			ΔT 50°C	ΔT 30°C
CR/HER3/500	500	60	53	27
CR/HER3/650	650	60	73	37.2
CR/HER3/750	750	60	88	44.9

Dimensions and Thermal Outputs | 4 COLUMN

CODE	HEIGHT (mm)	WIDTH (mm)	OUTPUT (WATTS)	
			ΔT 50°C	ΔT 30°C
CR/HER4/500	500	60	70	35.7
CR/HER4/650	650	60	94	47.9
CR/HER4/750	750	60	110	56.1

This product is Made to Measure, the ratings in the above table refer to 1 section only.

