Designer Radiators
and Towel Rails

DECLARATION OF PERFORMANCE

Loxley

Ref: 2026-574

DECLARATION OF PERFORMANCE | 2026-574

1.	**Unique identification code or name:**	Loxley
2.	**Intended use:**	Heating systems in buildings
3.	**Registered name:**	Double Quick (Heating) Ltd Units 3 & 4 St Helens House St Helens Way, Thetford, Norfolk IP24 1HG.
4.	**Systems of assessment:**	System 3
5.	**Harmonised standard:**	BS EN 442-1:2014
5a.	**Testing facility:**	Turkish Standards Institution (TSE), Necatibey Caddesi No: 112, 06100 Bakanlıklar, Çankaya / Ankara, Turkey. No. 1783
5b.	**Test Report No:**	003828-TSE-03/04

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	A1
Release of dangerous substances	None
Maximum operating pressure	400
Pressure tightness	No leakage at 1,30 x MOP
Resistance to pressure	No breakage at 1,69 x MOP
Maximum surface temperature	110°C
Rated thermal outputs (per section)	Please see table below
Resistance against corrosion	Absence of surface corrosion after 100 h humidity
Resistance against minor impact	Class 0

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

S C Double
Managing Director

Dated January 2026

Dimensions and Thermal Outputs |

CODE	HEIGHT (mm)	WIDTH (mm)	OUTPUT (WATTS)	
			ΔT 50°C	ΔT 30°C
CR/LOX/470	470	76	91	46.4
CR/LOX/770	768	76	144	73.4
CR/LOX/970	970	76	179	91.3

This product is Made to Measure, the ratings in the above table refer to 1 section only.