

# DECLARATION OF PERFORMANCE

Modus - Made to measure

Ref: 2026-577



|     |                                     |                                                                                                            |
|-----|-------------------------------------|------------------------------------------------------------------------------------------------------------|
| 1.  | Unique identification code or name: | Modus - Made to measure                                                                                    |
| 2.  | Intended use:                       | Heating systems in buildings                                                                               |
| 3.  | Registered name:                    | Double Quick (Heating) Ltd<br>Units 3 & 4 St Helens House<br>St Helens Way, Thetford, Norfolk<br>IP24 1HG. |
| 4.  | Systems of assessment:              | System 3                                                                                                   |
| 5.  | Harmonised standard:                | BS EN 442-1:2014                                                                                           |
| 5a. | Testing facility:                   | WSPLab Dr.-Ing. Frank Bitter, Kapuzinerweg 7, 70374<br>Stuttgart, Germany - No. 1428                       |
| 5b. | Test Report No:                     | 07.50.ZEH.053                                                                                              |

| ESSENTIAL CHARACTERISTICS           | PERFORMANCE                                       |
|-------------------------------------|---------------------------------------------------|
| Reaction to fire                    | A1                                                |
| Release of dangerous substances     | None                                              |
| Maximum operating pressure          | 1000                                              |
| Pressure tightness                  | No leakage at 1,30 x MOP                          |
| Resistance to pressure              | No breakage at 1,69 x MOP                         |
| Maximum surface temperature         | 110°C                                             |
| Rated thermal outputs (per section) | Please see table below                            |
| Resistance against corrosion        | Absence of surface corrosion after 100 h humidity |
| Resistance against minor impact     | Class 0                                           |

*The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.*

*Signed for and on behalf of the manufacturer by:*

S C Double  
Managing Director



Dated January 2026



## Dimensions and Thermal Outputs | 2 COLUMN

| CODE         | HEIGHT<br>(mm) | WIDTH<br>(mm) | OUTPUT (WATTS)  |                 |
|--------------|----------------|---------------|-----------------|-----------------|
|              |                |               | $\Delta T$ 50°C | $\Delta T$ 30°C |
| Modus 2.300  | 300            | 46            | 22              | 11.2            |
| Modus 2.350  | 350            | 46            | 25              | 12.8            |
| Modus 2.400  | 400            | 46            | 28              | 14.3            |
| Modus 2.450  | 450            | 46            | 33              | 16.8            |
| Modus 2.500  | 500            | 46            | 37              | 18.9            |
| Modus 2.550  | 550            | 46            | 41              | 20.9            |
| Modus 2.600  | 600            | 46            | 44              | 22.4            |
| Modus 2.750  | 750            | 46            | 55              | 28.1            |
| Modus 2.900  | 900            | 46            | 67              | 34.2            |
| Modus 2.1000 | 1000           | 46            | 73              | 37.2            |
| Modus 2.1100 | 1100           | 46            | 79              | 40.3            |
| Modus 2.1200 | 1200           | 46            | 86              | 43.9            |
| Modus 2.1500 | 1500           | 46            | 106             | 54.1            |
| Modus 2.1800 | 1800           | 46            | 125             | 63.8            |
| Modus 2.2000 | 2000           | 46            | 140             | 71.4            |
| Modus 2.2200 | 2200           | 46            | 154             | 78.5            |
| Modus 2.2500 | 2500           | 46            | 174             | 88.7            |
| Modus 2.2800 | 2800           | 46            | 195             | 99.5            |
| Modus 2.3000 | 3000           | 46            | 209             | 106.6           |

*This product is Made to Measure, the ratings in the above table refer to 1 section only.*



## Dimensions and Thermal Outputs | 3 COLUMN

| CODE         | HEIGHT<br>(mm) | WIDTH<br>(mm) | OUTPUT (WATTS)  |                 |
|--------------|----------------|---------------|-----------------|-----------------|
|              |                |               | $\Delta T$ 50°C | $\Delta T$ 30°C |
| Modus 3.300  | 300            | 46            | 31              | 15.8            |
| Modus 3.350  | 350            | 46            | 36              | 18.4            |
| Modus 3.400  | 400            | 46            | 41              | 20.9            |
| Modus 3.450  | 450            | 46            | 46              | 23.5            |
| Modus 3.500  | 500            | 46            | 51              | 26              |
| Modus 3.550  | 550            | 46            | 55              | 28.1            |
| Modus 3.600  | 600            | 46            | 60              | 30.6            |
| Modus 3.750  | 750            | 46            | 75              | 38.3            |
| Modus 3.900  | 900            | 46            | 89              | 45.4            |
| Modus 3.1000 | 1000           | 46            | 98              | 50              |
| Modus 3.1100 | 1100           | 46            | 107             | 54.6            |
| Modus 3.1200 | 1200           | 46            | 116             | 59.2            |
| Modus 3.1500 | 1500           | 46            | 143             | 72.9            |
| Modus 3.1800 | 1800           | 46            | 170             | 86.7            |
| Modus 3.2000 | 2000           | 46            | 189             | 96.4            |
| Modus 3.2200 | 2200           | 46            | 208             | 106.1           |
| Modus 3.2500 | 2500           | 46            | 236             | 120.4           |
| Modus 3.2800 | 2800           | 46            | 262             | 133.6           |
| Modus 3.3000 | 3000           | 46            | 281             | 143.3           |

*This product is Made to Measure, the ratings in the above table refer to 1 section only.*



## Dimensions and Thermal Outputs | 4 COLUMN

| CODE         | HEIGHT<br>(mm) | WIDTH<br>(mm) | OUTPUT (WATTS)  |                 |
|--------------|----------------|---------------|-----------------|-----------------|
|              |                |               | $\Delta T$ 50°C | $\Delta T$ 30°C |
| Modus 4.300  | 300            | 46            | 40              | 20.4            |
| Modus 4.350  | 350            | 46            | 47              | 24              |
| Modus 4.400  | 400            | 46            | 52              | 26.5            |
| Modus 4.450  | 450            | 46            | 58              | 29.6            |
| Modus 4.500  | 500            | 46            | 65              | 33.2            |
| Modus 4.550  | 550            | 46            | 71              | 36.2            |
| Modus 4.600  | 600            | 46            | 77              | 39.3            |
| Modus 4.750  | 750            | 46            | 95              | 48.5            |
| Modus 4.900  | 900            | 46            | 112             | 57.1            |
| Modus 4.1000 | 1000           | 46            | 124             | 63.2            |
| Modus 4.1100 | 1100           | 46            | 136             | 69.4            |
| Modus 4.1200 | 1200           | 46            | 147             | 75              |
| Modus 4.1500 | 1500           | 46            | 180             | 91.8            |
| Modus 4.1800 | 1800           | 46            | 214             | 109.1           |
| Modus 4.2000 | 2000           | 46            | 237             | 120.9           |
| Modus 4.2200 | 2200           | 46            | 260             | 132.6           |
| Modus 4.2500 | 2500           | 46            | 295             | 150.5           |
| Modus 4.2800 | 2800           | 46            | 328             | 167.3           |
| Modus 4.3000 | 3000           | 46            | 351             | 179             |

*This product is Made to Measure, the ratings in the above table refer to 1 section only.*



Dimensions and Thermal Outputs | 5 COLUMN

| CODE         | HEIGHT<br>(mm) | WIDTH<br>(mm) | OUTPUT (WATTS)  |                 |
|--------------|----------------|---------------|-----------------|-----------------|
|              |                |               | $\Delta T$ 50°C | $\Delta T$ 30°C |
| Modus 5.300  | 300            | 46            | 48              | 24.5            |
| Modus 5.350  | 350            | 46            | 56              | 28.6            |
| Modus 5.400  | 400            | 46            | 64              | 32.6            |
| Modus 5.450  | 450            | 46            | 72              | 36.7            |
| Modus 5.500  | 500            | 46            | 80              | 40.8            |
| Modus 5.550  | 550            | 46            | 87              | 44.4            |
| Modus 5.600  | 600            | 46            | 95              | 48.5            |
| Modus 5.750  | 750            | 46            | 117             | 59.7            |
| Modus 5.900  | 900            | 46            | 138             | 70.4            |
| Modus 5.1000 | 1000           | 46            | 151             | 77              |
| Modus 5.1100 | 1100           | 46            | 165             | 84.2            |
| Modus 5.1200 | 1200           | 46            | 179             | 91.3            |
| Modus 5.1500 | 1500           | 46            | 215             | 109.7           |
| Modus 5.1800 | 1800           | 46            | 256             | 130.6           |
| Modus 5.2000 | 2000           | 46            | 282             | 143.8           |
| Modus 5.2200 | 2200           | 46            | 308             | 157.1           |
| Modus 5.2500 | 2500           | 46            | 347             | 177             |
| Modus 5.2800 | 2800           | 46            | 385             | 196.4           |
| Modus 5.3000 | 3000           | 46            | 413             | 210.6           |

This product is Made to Measure, the ratings in the above table refer to 1 section only.



Dimensions and Thermal Outputs | 6 COLUMN

| CODE         | HEIGHT<br>(mm) | WIDTH<br>(mm) | OUTPUT (WATTS)  |                 |
|--------------|----------------|---------------|-----------------|-----------------|
|              |                |               | $\Delta T$ 50°C | $\Delta T$ 30°C |
| Modus 6.300  | 300            | 46            | 57              | 29.1            |
| Modus 6.350  | 350            | 46            | 66              | 33.7            |
| Modus 6.400  | 400            | 46            | 75              | 38.3            |
| Modus 6.450  | 450            | 46            | 84              | 42.8            |
| Modus 6.500  | 500            | 46            | 94              | 47.9            |
| Modus 6.550  | 550            | 46            | 103             | 52.5            |
| Modus 6.600  | 600            | 46            | 113             | 57.6            |
| Modus 6.750  | 750            | 46            | 137             | 69.9            |
| Modus 6.900  | 900            | 46            | 163             | 83.1            |
| Modus 6.1000 | 1000           | 46            | 180             | 91.8            |
| Modus 6.1100 | 1100           | 46            | 195             | 99.5            |
| Modus 6.1200 | 1200           | 46            | 209             | 106.6           |
| Modus 6.1500 | 1500           | 46            | 250             | 127.5           |
| Modus 6.1800 | 1800           | 46            | 297             | 151.5           |
| Modus 6.2000 | 2000           | 46            | 330             | 168.3           |
| Modus 6.2200 | 2200           | 46            | 359             | 183.1           |
| Modus 6.2500 | 2500           | 46            | 403             | 205.5           |
| Modus 6.2800 | 2800           | 46            | 449             | 229             |
| Modus 6.3000 | 3000           | 46            | 481             | 245.3           |

This product is Made to Measure, the ratings in the above table refer to 1 section only.

