

DECLARATION OF PERFORMANCE

Bench

Ref: 2026-578



1.	Unique identification code or name:	Bench
2.	Intended use:	Heating systems in buildings
3.	Registered name:	Double Quick (Heating) Ltd Units 3 & 4 St Helens House St Helens Way, Thetford, Norfolk IP24 1HG.
4.	Systems of assessment:	System 3
5.	Harmonised standard:	BS EN 442-1:2014
5a.	Testing facility:	WSPLab Dr.-Ing. Frank Bitter, Kapuzinerweg 7, 70374 Stuttgart, Germany - No. 1428
5b.	Test Report No:	07.50.ZEH.053

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	A1
Release of dangerous substances	None
Maximum operating pressure	1000
Pressure tightness	No leakage at 1,30 x MOP
Resistance to pressure	No breakage at 1,69 x MOP
Maximum surface temperature	110°C
Rated thermal outputs	Please see table below
Resistance against corrosion	Absence of surface corrosion after 100 h humidity
Resistance against minor impact	Class 0

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

S C Double
Managing Director



Dated January 2026



Dimensions and Thermal Outputs |

CODE	HEIGHT (mm)	WIDTH (mm)	OUTPUT (WATTS)	
			ΔT 50°C	ΔT 30°C
BENCH5/700	434	700	565	291
BENCH5/850	434	850	685	353
BENCH5/1000	434	1000	815	420
BENCH5/1300	434	1300	1045	538
BENCH5/1600	434	1600	1250	644
BENCH5/1900	434	1900	1485	765
BENCH5/2100	434	2100	1650	850
BENCH5/2600	434	2600	2015	1038
BENCH5/2900	434	2900	2245	1156
BENCH6/700	480	700	678	349
BENCH6/850	480	850	822	423
BENCH6/1000	480	1000	978	504
BENCH6/1300	480	1300	1254	646
BENCH6/1600	480	1600	1500	773
BENCH6/1900	480	1900	1782	918
BENCH6/2100	480	2100	1980	1020
BENCH6/2600	480	2600	2418	1245
BENCH6/2900	480	2900	2694	1387